

QT-7300 Stay in Touch with Your Business

The PC-based QT-7300 features a large 12.1-inch touch-screen terminal, easy expandability and high-speed Ethernet LAN exchange for optimum management of hospitality, fast-food, retail or grocery POS data.

QT-7300 Touch Screen Terminal



CASIO[®]
the unexpected extra™

QT-7300 **Large, clear touch-screen display and Windows® compatibility for optimum operating ease and versatility**

Highlight Features

System configured for today's businesses

With its 850 MHz CPU and ample memory/hard disk capacity, the QT-7300 is ideally equipped for efficient business operation. Its high-speed 100-base-T Ethernet capability strengthens the communication function and enhances operating friendliness

Dual display capability

A QT-7300 VGA port provides an expansion PC monitor connection for a customer display. This system can display data on both the LCD and the expansion PC monitor separately or simultaneously. The full contents of customer purchases and store advertising, etc., can be displayed on the expansion PC monitor.

Compact, rugged design

A lower profile frees space for other uses. Designed by POS experts for POS professionals, the QT-7300 is suitable for various applications.

Specifications

Large touch screen

A 12.1" TFT touch screen with 800 x 600 SVGA resolution affords a wider viewing angle and easier entry operation via graphical user interface. IPX1 water splash proof construction protects the touch panel from damage by wet hand operation or water spills.

Various I/O interfaces for flexible expandability

- Ethernet 10/100-Base-T
- Three RS-232C ports
- Two USB ports
- One parallel port
- One PCI (half-size card) expansion slot
- Two drawer ports

Supported Operating Systems:

Windows® 98/2000

Processor	Intel® Celeron 850 MHz
Memory (standard)	128 MB DIMM type
Hard disk	2.5 inch 10 GB or higher
External FDD interface	3.5" (1.44 MB)
Expansion slot	One PCI (half-size card)
Video controller	SVGA
Touch panel	Analogue resistive film input
Water splash proof touch panel	IPX1
Display	12.1" color TFT
Ethernet port	10 / 100-Base-T
RS232C ports	3
Parallel port	1
VGA port	1
PS/2 keyboard port	1
PS/2 mouse port	1
USB ports	2
Drawer ports	2
Desktop base	1 set
Cable management shroud	1 set
Physical Environment	
Dimensions of main body (WxHxD)	360 x 82 x 340 mm
Weight of main body	4.7 kg
Operating temperature range	5 - 35°C
Operating humidity range	10 - 85 %RH

Options	
Description	Model Name
Customer display with attachment to main unit	QT-7360D
Customer display and pole (20 cm high) with attachment to main unit	QT-7362D
Customer display and stand	QT-7363D



QT-7363D